

HelloWorld.vn

Khang Ngá»c

D series Electronical Control Valve

[LiÃn há»±](#)




Controller Specifications	
Controller Material	NORYL® Plastic
Inlet/Outlet Fittings	3/4" or 1"NPTF
Cycles	5
Regeneration	Down Flow or Up Flow
Flow Rate-Valve Only	
Service @ 15psi Drop	20gpm
Peak Service @ 25psi Drop	26gpm
CV Service @ 1 psi Drop	5.2
Peak Backwash @ 25 psi Drop	15gpm
Regeneration	
Adjustable	All position
Time area	1-999 Mins / Position
Meter	
Accuracy	0.75-15gpm±2%
Capacity Options	1-9999999 gal or m3
Dimension	
Distributor Pilot	1.05"O.D.
Drain Line	1/2"
Brine Line	3/8"
Mounting Base	2-1/2"-8NPSM
Height from top of tank	7.8" or 198mm
Flow Rate-System@15psi Drop	
8**44"@0.75cf resin	9.5gpm
9**48"@1cf resin	11.5gpm
10**54"@1.5cf resin	11.6gpm
12**48"@2cf resin	12.6gpm
Operation	
Supply Voltage - Frequency	110V,220V-50Hz,60Hz
Max AV	8.4W
Pressure	Hydrostatic:300psi
	Working:20-125psi
Temperature	1°C-43°C
Shipping Weight	Timer Type:2Kg or 4.4lbs
	Meter Type:2.4Kg or 5.3lbs
Option	
Hard-water Type or None Hard-water Type (Regeneration)	
Down Flow or Up Flow	

D series Electrical Control Valve Model

D-STC	D series Electrical Softener Timer Control Valve
D-SMM	D series Electrical Softener Meter Control Valve
D-FTC	D series Electrical Filter Timer Control Valve
D-FMM	D series Electrical Filter Meter Control Valve

Download:

Service Manual: 

Brochure: 

[ThÃng tin ngÆ°á»i bÃjn hÃng](#)

Nhá»n xÃ©t cá»sa khÃjch hÃng: ChÆ°a cÃ³ bÃnh luá»n nÃ o cho sá»n phá»m nÃ y.
HÃy login rá»i viá»t bÃnh luá»n.