

F11 series Mechanical Control Valve

Viết bởi Administrator

Thứ ba, 22 Tháng 2 2011 10:05 - Lần cập nhật cuối Thứ hai, 06 Tháng 4 2015 09:24

Van điều khiển Fobrite.



F11 series Mechanical Control Valve

Vietbi Administrator

Thứ ba, 22 Tháng 2 2011 10:05 - Lần cập nhật cuối: Thứ hai, 06 Tháng 4 2015 09:24

Controller Specifications	
Controller Material	NORYL® Plastic
Inlet/Outlet Fittings	3/4" or 1"NPTF
Cycles	7
Regeneration	Down Flow
Flow Rate-Valve Only	
Service @ 15psi Drop	20gpm
Peak Service @ 25psi Drop	26gpm
Peak Backwash @ 25psi Drop	7gpm
CV Service @ 1 psi Drop	5
CV Backwash @ 1 psi Drop	1.8
Flow Rate-System@15psi Drop	
8"*44"@0.75cf resin	9.5gpm
9"*48"@1cf resin	11.5gpm
10"*54"@1.5cf resin	11.6gpm
12"*48"@2cf resin	12.6gpm
Meter	
Accuracy	0.25-15gpm±5%
Capacity Options	Standard: 2100G or 8 T
	Extended: 10800G or 40 T
Dimension	
Distributor Pilot	1.05"O.D.
Drain Line	1/2"
Brine Line	3/8"
Mounting Base	2-1/2"-8NPSM
Height from top of tank	7" or 178mm
Operation	
Supply Voltage - Frequency	110V,220V-50Hz,60Hz
Max AV	3W
Pressure	Hydrostatic:300psi
	Working:20-125psi
Temperature	1°C-43°C
Shipping Weight	Timer Type:1.7Kg or 3.8lbs
	Meter Type:2Kg or 4.4lbs

F11 series Mechanical Control Valve

Việt b... Administrator

Thứ ba, 22 Tháng 2 2011 10:05 - Lần cập nhật cuối: Thứ hai, 06 Tháng 4 2015 09:24

F11 series Mechanical Control Valve Model

F11-STC	F11 series Mechanical Softener Timer Control Valve
F11-SMM	F11 series Mechanical Softener Meter Control Valve
F11-FTC	F11 series Mechanical Filter Timer Control Valve
F11-FMM	F11 series Mechanical Filter Meter Control Valve

Download:
Service Manual:
Brochure:

